

In the Claims:

Cancel claims 1-4, 10 and 11 without prejudice.

1. (Cancelled)

2. (Cancelled)

3. (Cancelled)

4. (Cancelled)

5. (Original) A body for an access port for insufflating a surgical

site, comprising:

the body including a central bore therethrough from a distal end to a proximal end thereof and including on an outer wall thereof near the distal end an attachment site for an inflatable balloon;

a fluid passage within a wall of the body communicating with the attachment site and with a fluid inlet to form a fluid channel for selectively inflating a balloon at the attachment site with fluid under pressure supplied to the inlet;

the body including near the proximal end thereof an attachment rim for receiving thereat a resilient sealing member to form a fluid-tight seal with the body and with an aperture therein substantially aligned with central bore; and

the body including an insufflation inlet disposed intermediate the distal and proximal ends in communication with the central bore.

6. (Original) The body of an access port according to claim 5 including a section intermediate the proximal and distal ends for transitioning from the central bore near the distal end to a larger internal bore near the proximal end.

7. (Original) The body of an access port according to claim 6 in which the insufflation inlet communicates with the central bore and larger internal bore within the transition section.

8. (Original) The body of an access port according to claim 6 in which the fluid inlet is disposed proximate the transition section of the body and near the insufflation inlet.

9. (Original) The body of an access port according to claim 5 in which the attachment rim includes a recessed groove within an outer wall of the body near the proximal end thereof for receiving a resilient sealing member therein in fluid-tight seal with the body.

10. (Cancelled)

11. (Cancelled)

12. (Original) A sealing member for an insufflation access port having a body with a central bore therethrough between distal and proximal

ends thereof, the sealing member for attachment to the proximal end of the body, comprising:

a hollow cylinder of resilient material having a distal end disposed to insert within the central bore of the body at the proximal end thereof and including an outwardly extending flange integrally formed on the proximal end of the cylinder to overlay the proximal end of the body, the flange including an aperture therethrough in position to substantially align with the central bore of the body upon attachment thereto for receiving therein an endoscopic instrument in fluid-tight sliding sealing engagement within the aperture.

13. (Original) The sealing member according to claim 12 for attachment to the body of an access port having a recessed groove about the periphery of the body near the proximal end thereof, the flange of the sealing member comprising:

a substantially cylindrical section extending substantially concentrically with the hollow cylinder toward the distal end thereof to overlay the proximal end of the body and terminate with an inwardly intruding rim integrally formed with the cylinder section and the flange and the hollow cylinder, said rim being dimensioned and positioned to engage

the recessed groove about the periphery of the body in fluid-tight sealing engagement therein.

14. (Original) The sealing member according to claim 12 including a protruding ring integrally formed about the cylinder near the distal end thereof for deforming within the central bore of the body to form a fluid-tight seal therewith.

15. (Original) The sealing member according to claim 12 including an intruding ring integrally formed on said intruding rim for deforming within the recessed groove to form a fluid-tight seal therein.

16. (Original) An auxiliary sealing member for insertion within the aperture of the sealing member of claim 12, comprising:

a hollow cylinder of resilient material including an end segment integrally formed on a proximal end of the cylinder having an aperture therethrough, and having an outwardly protruding flange integrally formed about a distal end thereof, the hollow cylinder of the auxiliary sealing member being dimensioned to form a fluid-tight seal within the aperture of the sealing member, and the protruding flange on the distal end of the auxiliary sealing member being disposed to engage the distal end of the sealing member for retaining the auxiliary sealing member within the aperture of the sealing member.

17. (Previously Added) Fluid sealing apparatus for operation with an endoscopic instrument at a surgical site, the apparatus comprising:

a body having a central bore dimensioned to receive an endoscopic instrument therein, the bore extending through the body between distal and proximal ends thereof;

a balloon of substantially toroidal-shape disposed about the body near the distal end thereof for selectively expanding laterally outwardly about the body;

a fluid passage in a wall of the body in communication with the balloon and extending along the wall toward the proximal end of the body for connection near the proximal end to a source of fluid under pressure to selectively inflate the balloon; and

a fluid seal disposed about the body near the proximal end thereof having an aperture therethrough substantially aligned with the central bore through the body, and having an inner dimension resiliently and flexibly disposed to receive an endoscopic instrument therein in sliding fluid-sealing engagement therewith.